

SafeTap Plus Environmentally-Safe Lubricant

(Revision: January 16, 2001)

APPLICATIONS

- Safe Tap Plus is safe for use on all metals, except magnesium.
- Formulated with water-soluble synthetic lubricants, Safe Tap Plus provides the cooling properties of a water-soluble coolant with the viscosity of a straight oil.
- Safe Tap Plus contains no mineral oils or solvents, so there is no oily residue.
- Water-soluble tapping fluid; not recommended for microlubrication applicators.
- Safe Tap Plus outperforms many competitors' oil-based fluids in lubricity testing.

MATERIALS COMPATIBILITY

- Safe for all metals.

HEALTH AND SAFETY

- Safe Tap Plus contains no hazardous ingredients subject to the reporting requirements of 29 CFR 1910.1200 (OSHA's Hazard Communication Standard).
- Refer to MSDS (Material Safety Data Sheet) for complete information on health and safety.

For MSDS
call our
"Fax on Demand"
(800) 452-5823 Ext.1
or visit our website
www.itwfpg.com

AVAILABLE IN:

4 oz.:	71910
16 oz.:	71912
1 Gallon:	71913
5 Gallon:	71914

PHYSICAL PROPERTIES

Appearance:	Transparent medium golden viscous fluid
Specific gravity:	1.01
Density:	8.40 pounds per gallon
Viscosity:	30 centistokes @ 25°C (77°F)
Active sulfur content:	none
Total chlorine content:	none
Silicones:	none
VOC level:	0.0%
Flash point:	greater than 200°F
Mineral oil content:	0.0%

TW Fluid Products Group

3624 West Lake Avenue • Glenview, IL 60025
(800) 452-5823 • Fax (800) 952-5823
(847) 657-2578 • Fax (847) 657-4897

www.itwfpg.com