

SafeTap Ultima

(Revision: January 16, 2001)

APPLICATIONS

- A high performance, safe tapping fluid that has been proven to be as effective as tapping fluids containing 1,1,1-trichlorethane.
- Works on all metals.
- All natural ingredients.
- Non-staining and odorless.

MATERIALS COMPATIBILITY

- Safe for all metals.

AVAILABLE IN:

4 oz.:	71951
8 oz.:	71956
16 oz.:	71952
1 Gallon:	71953
5 Gallon:	71954

HEALTH AND SAFETY

- SafeTap Ultima contains no hazardous ingredients subject to the reporting requirements of 29 CFR 1910.1200 (OSHA's Hazard Communication Standard).
- Refer to MSDS (Material Safety Data Sheet) for complete information on health and safety.

PHYSICAL PROPERTIES

Appearance:	Transparent viscous oil
Specific gravity:	0.93
Density:	7.74 lbs./gallon
Active sulfur content:	None
Total chlorine content:	None
Silicones:	None
VOC level:	0.0%
Flash point:	418°F
Mineral oil content:	None

For MSDS
call our
"Fax on Demand"
(800) 452-5823 Ext.1
or visit our website
www.itwfpg.com

TW Fluid Products Group

3624 West Lake Avenue • Glenview, IL 60025

(800) 452-5823 • Fax (800) 952-5823

(847) 657-2578 • Fax (847) 657-4897

www.itwfpg.com